



590.SGE10005.SN

SWITCH DISCONNECTOR

100A 3P+SN IP65 150x220x120mm Y4 IK10
GENERAL GREY/BLACK SN (SOLID NEUTRAL)

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|----------------------------|-----------------------------------|---|
| Product type | SWITCH DISCONNECTOR | EN 60947-3 (2009) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Commercial series | ISOLATORS-INOX Series | | |
| Synthetical description | SWITCH DISCONNECTOR | EN 60947-1 (2007) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Material | STAINLESS STEEL [AISI304L] | EN 60947-1/A1 (2011) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Protection degree IP | IP65 | EN 60947-3/A1 (2012) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Type | GENERAL | | |
| Colour | GREY/BLACK | EN 60947-1/A2 (2014) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Rated current | 100A | | |
| Poles | 3P+SN | EN 60947-3/A2 (2015) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Switch size | Y4 | | |
| Rated voltage | 690V | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Dimensions | 150x220x120mm | | |
| Notes | SN (SOLID NEUTRAL) | | |
| Protection degree IK | IK10 | | |